

## A5 EVO

**NEW**



### Standard equipment



- 5.511.1097  
PPL brush Ø 483 mm - 19"



- 4.508.X468  
Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
- 4.508.X467  
Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



- 0.108.0042  
On-board Battery charger  
CBHD1 24V 10A  
only for model code:  
8.527.0007 - 8.527.0008  
8.527.0013



- 0.107.0054  
Maintenance free battery  
12V 75Ah BT DC 5.5  
only for model code:  
8.527.0013

### Other available versions:

- 8.527.0013 - A5 Evo 50B with batteries and battery charger
- 8.527.0007- A5 Evo 50B with battery charger

## A5 EVO

- Very compact scrubbing machines suitable to work for the maintenance cleaning of limited-size areas (up to 1.500 m<sup>2</sup>)
- Especially suitable for cleaning: car shops, sales points, gym, health care
- Control panel with operator presence safety system
- Low level battery indicator: brush/vacuum and traction progressive cut off
- Solution water filter and solenoid valve (battery model only)
- Easy access to the battery compartment
- Quick drain and easily inspectable recovery tank
- Non-marking wheels
- Roto-molded polyethylene tanks, shock and acid resistant
- The lower tank also serves as battery compartment
- Low noise operation thanks to the protected positioning of vacuum motor.

Technical data:	A5 EVO 50 E	A5 EVO 50	A5 EVO 50 T
Code	8.527.0005	8.527.0006	8.527.0008
power supply	230 V - 50 Hz	24V	24V
scrubbing width	500 mm	500 mm	500 mm
squeegee width	800 mm	800 mm	800 mm
max working capacity	2000 m <sup>2</sup> /h	2000 m <sup>2</sup> /h	2000 m <sup>2</sup> /h
detergent tank capacity	44 l	44 l	44 l
recovery tank capacity	50/60 l	50/60 l	50/60 l
traction	mechanical	mechanical	automatic
vacuum motor	1000W	480W	480W

# Floor scrubber-driers



Powerful gearmotor; brush plate with integrated plastic splash guard/bumper. The outflow of the detergent solution is controlled by a solenoid valve. The actuation of the solenoid valve is operated by the control lever, avoiding the detergent solution outflow

when the brush is stopped during the interruptions of work. Renovated squeegee with new pressure adjusting system. The squeegee blades are easily replaceable without the use of tools. Quick and easy squeegee coupling through the two large knobs; the



squeegee is released without any damage in the event of accidental impact. Mesh filter to retain possible solid pieces, protects the solenoid valve. The filter also has the function of regulating the outflow of the cleaning solution; screwing the

transparent cover increases the amount of flow, while unscrewing the cover reduces the flow.



## Optional accessories:



- 2 x 0.107.0002  
Tubular battery Pb-acid  
12V 118Ah C5



- 2 x 0.107.0063  
GEL Battery 12 MFP 105  
12V 105Ah C5



- 4.508.1178 Polyurethane  
front blade L.830 TH. 3
- 4.508.1177 Polyurethane  
rear blade L.870 TH. 4



- 5.511.1098  
Tynex brush Ø 483 mm-19"
- 5.511.1128  
PPL 0,03 brush Ø 483 mm-19"
- 5.511.1206  
PES brush Ø 483 mm - 19"



- 5.511.1099  
EWU pad driver Ø 483  
mm-19"



- 6.508.0034  
Abrasive pad Ø 483 mm-19"  
- beige
- 6.508.0041  
Abrasive pad Ø 483 mm-19"  
- green
- 6.508.0048  
Abrasive pad Ø 483 mm-19"  
- black



- 4.512.0068  
Extension electric cord 15 m  
with Schuko plug